

Technical Specifications for CDS-FT17T

TOUCH SCREEN THIN CLIENT



California Designs & Systems, Inc.

The CDS-FT17T Industrial Splash-Proof Touch Screen Thin Client: Color 17" LCD Display Shielded Splash-Proof & Dust-Proof Resistive Touch Screen TFT-Active 1280x1024 75Hz 300cd/m2 800:1 5ms 0.264mmDot AMD GX III LX800 500MHz Geode CS5536 Chipsets Browser IE 6.0 Flash Memory 256MB (exp to 8Gb) RAM-512Mb (exp 1Gb) DDR SO-DIMM 1xSerial 1xParallel 1xVGA 4xUSB2.0 2xPS/2 Ports Remote Management Software Protocols RDP 5.2/ICA 8.1 Terminal Emulation Optional Heavy Duty All Aluminum Construction Custom Silver Spatter Finish VESA & Side Mount Windows Embedded CE



MODEL	CDS-FT17T	
MAIN BOARD		
CPU/CODE:	AMD GX III LX800 500MHz	
CORE LOGIC:	Geode CS5536 Chipsets	
SYSTEM MEMORY:	256MB DDR SO-DIMM Expandable to 1GB	
OS SUPPORT:	Windows-XP Windows-XPe WEPOS WinCE Linux	
DISPLAY		
TFT LCD:	17"	
BRIGHTNESS:	300cd/m2	
RESOLUTION:	10280 x 1024 (75Hz 800:1 5ms 0.264mm)	
TOUCH SCREEN:	5-Wire Resistive Type	
STORAGE DEVICES		
HARD DISK DRIVE:	1 x 2.5" HDD Drive Bay	
COMPACT FLASH:	256MB Expandable to 8GB	
I/O PORTS		
SERIAL PORTS:	1 x Serial RS323 COM 1: DB-9 RS-232 Pin9 w/RI/5V/12V 2 x PS/2 Ports	
USB:	4 x USB2.0	
LAN:	1 x Gigabit Ethernet RJ45	
CASH DRAWER:	Optional	
AUDIO:	Optional	
TERMINAL EMULATION:	Optional	
OTHERS		
SOFTWARE:	Remote Management 6.0 SP1	
WALL MOUNT:	Supports VESA Mount	
POWER INPUT:	External adapter, 9-Watt, 19VDC Input	
UPS POWER BACKUP:	Supports Smart Battery 4S1P Backup Function	
COLOR:	Custom Silver Splatter	
MATERIAL:	All Aluminum Chassis	
EMC & SAFETY COMPLIANCE	FCC / CE / WEEE /RoHS	
WEIGHT:	15Lbs	
DIMENSIONS:	15"W x 13"H x 3.5"D	
OPERATING TEMPERATURE:	0°C (32°F) ~ 50°C (122°F)	
STORAGE TEMPERATURE:	-20°C (-68°F) ~ 60°C (140°F)	
HUMIDITY:	20% - 85% RH, non-condensing	
WARRANTY:	One Year Parts and Labor	
Call: 1(800)588-9609	email: solutions@cdspanther.com	www.cdspanther.com